

MATERIAL SAFETY
DATA SHEET

Betterbilt Chemical
3137 26th Street
Los Angeles Ca 90023
(323) 266-7111

24-HOUR
EMERGENCY
TELEPHONE
(800) 255-3924

Rust Proofer

PRODUCT ID NO.: 33918

PAGE: 1

EFFECTIVE DATE: 01/15/10
PRODUCT ID NO.: 33918
DATE PREPARED: 02/04/11

=====
This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.
=====

This MSDS complies with 29 CFR 1910.1200
(The Hazard Communication Standard)

=====
SECTION I - PRODUCT IDENTIFICATION
=====

PRODUCT DESCRIPTION: THE MASTER'S TOUCH M-1 AEROSOL

D.O.T. PROPER SHIPPING NAME: ORM-D

CONSUMER COMMODITY

NFPA CODES: HEALTH - 2 FLAMMABILITY - 3 CORROSIVE - 0 REACTIVITY - 0

=====
SECTION II - COMPONENTS
=====

XYLENE

* PEL: 100 ppm

CAS #: 1330-20-7

TLV: 100 ppm

ACRYLIC RESIN

PEL: NOT DETERMINED

CAS #: 28262-63-7

TLV: NOT DETERMINED

ACETONE

* PEL: TWA 1000 PPM

CAS #: 67-64-1

TLV: TWA 750 PPM STEL 1000 PPM

p-Chlorobenzotrifluoride

PEL: NOT ESTABLISHED

CAS #: 98-56-6

TLV: NOT ESTABLISHED

HYDROCARBON PROPELLANT

PEL: 800 PPM

CAS #: 68476-86-8

TLV: 800 PPM

"*" If present, IARL, NTP and OSHA carcinogens and chemical subject to this reporting requirements of SARA TITLE III, SECTION 313 are identified in this section.

=====
SECTION III - PHYSICAL DATA
=====

BOILING POINT FOR PRODUCT: N/D (NOT DETERMINED)

VAPOR PRESSURE FOR PRODUCT: N/D

VAPOR DENSITY FOR PRODUCT: AIR=1: 3.0

SPECIFIC GRAVITY: 0.95-0.99 @ 65 deg F

V.O.C.(GRAMS PER LITER): <250 LESS EXEMPT SOL

WATER SOLUBILITY: NEGLIGIBLE

MATERIAL SAFETY
DATA SHEET

Betterbilt Chemical
3137 26th Street
Los Angeles Ca 90023
(323) 266-7111

24-HOUR
EMERGENCY
TELEPHONE
(800) 255-3924

Rust Proofer

PRODUCT ID NO.: 33918

PAGE: 2

===== SECTION III - PHYSICAL DATA (CONTINUED) =====

APPEARANCE: CLEAR LIQUID

===== SECTION IV - FIRE AND EXPLOSION DATA =====

FLASH POINT(TCC): LEVEL 3 AEROSOL

EXPLOSIVE LIMIT (PRODUCT): LOWER - 1.0 UPPER - 6.0

SEC04.24

GENERAL HAZARD:

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint. Static Discharge, material can accumulate static charge which can cause an incendiary electrical discharge.

"Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. Empty containers should be completely drained, properly bunged and promptly returned to drum reconditioner, or properly disposed of.

FIRE FIGHTING:

Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boilover. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

HAZARDOUS COMBUSTION PRODUCTS: Fumes, smoke and carbon monoxide.

===== SECTION V - HEALTH HAZARD DATA =====

SEC05.24

GENERAL: This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: May cause eye injury which may persist for several days. Liquid and vapor in high concentrations, causes irritation, tearing and burning sensation.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: May be poisonous or fatal if swallowed. A Small amounts of this product can cause mental sluggishness, nausea and vomiting leading to severe illness, and may produce adverse effects on vision with possible blindness or death if treatment not received.

MATERIAL SAFETY
DATA SHEET

Betterbilt Chemical
3137 26th Street
Los Angeles Ca 90023
(323) 266-7111

24-HOUR
EMERGENCY
TELEPHONE
(800) 255-3924

Rust Proofer

PRODUCT ID NO.: 33918

PAGE: 3

===== SECTION V - HEALTH HAZARD DATA(CONTINUED) =====

FIRST AID

EYE CONTACT: Flush eyes with large amounts of water until irritation subsides.
If irritation persists, get medical attention.

SKIN CONTACT: Flush with large amounts of water; use soap if available.
Remove grossly contaminated clothing, including shoes, and leather
before reuse.

INHALATION: Using proper respiratory protection, immediately remove the
affected victim from exposure. Administer artificial respiration if
breathing is stopped. Keep at rest. Call for prompt medical attention

INGESTION: If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt
medical attention.

PRECAUTIONS

SPECIAL PRECAUTIONS: As a precaution, exposure to liquids, vapors,
mists or fumes should be minimized.

PERSONAL PROTECTION: For open systems where contact is likely, wear safety
glasses with side shields, long sleeves, and chemical resistant
gloves. Where concentrations in air may exceed the limits, work
practice or other means of exposure reduction are not adequate,
NIOSH/MSHA approved respirators may be necessary to prevent
overexposure by inhalation.

VENTILATION: The use of mechanical dilution ventilation is recommended
whenever this product is used in a confined space, is heated above
ambient temperatures, or is agitated.

(PROPOSITION 65): SEC05

State of California SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986.

WARNING: IN ACCORDANCE WITH PROP 65, THIS PRODUCT CONTAINS A
CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH
DEFECTS AND OTHER REPRODUCTIVE HARM.

===== SECTION VI - REACTIVITY DATA =====

SEC06.24

STABILITY: Stable

CONDITIONS TO AVOID INSTABILITY: Not applicable

HAZARDOUS POLYMERIZATION: Will not occur

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide

===== SECTION VII - SPILL OR LEAK PROCEDURES =====

SEC07.24

LAND SPILL: Eliminate sources of ignition. Prevent additional discharge of
material, if possible to do so without hazard. For small spills
implement cleanup procedures; for large spills implement cleanup
procedures and, if in public area, keep public away and advise
authorities. Also, if this product is subject to CERCLA reporting
notify the National Response Center. Prevent liquid from entering
sewers, watercourses, or low areas. Contain spilled liquid with sand

MATERIAL SAFETY
DATA SHEET

Betterbilt Chemical
3137 26th Street
Los Angeles Ca 90023
(323) 266-7111

24-HOUR
EMERGENCY
TELEPHONE
(800) 255-3924

Rust Proofer

PRODUCT ID NO.: 33918

PAGE: 4

=====
SECTION VII - SPILL OR LEAK PROCEDURES(CONTINUED) =====

or earth. Do not use combustible materials such as sawdust. Recover by pumping or with a suitable absorbant. Consult an expert on disposal regulations.

WATER SPILL: Eliminate sources of ignition warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear. Remove from surface by skimming or with suitable adsorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in non-confined waters. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulation.

=====
SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED =====

SEC08.24

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required.

Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing.

Standard work shoes; discard if shoes cannot be decontaminated.

Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

=====
SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS =====

SEC09.24

HANDLING AND STORAGE PRECAUTIONS: Store in a cool place. Do not expose to temperatures above 120 degree F. Keep away from heat, sparks and flame. Ventilation should be provided at the floor level. Do not store in pits, depressions, basements or unventilated areas.

In case of fire: use carbon dioxide, dry chemicals, water or foam.

Pressure-demand, self-contained breathing apparatus should be provided for fire fighters.

===== ADDITIONAL COMMENTS =====

MATERIAL SAFETY DATA SHEET	Betterbilt Chemical 3137 26th Street Los Angeles Ca 90023 (323) 266-7111	24-HOUR EMERGENCY TELEPHONE (800) 255-3924
-------------------------------	---	---

Rust Proofer

PRODUCT ID NO.: 33918 PAGE: 5

===== ADDITIONAL COMMENTS (CONTINUED) =====

CALIFORNIA AIR RESOURCE BOARD: This product complies with "REGULATION FOR REDUCING VOLATILE ORGANIC COMPOUND EMISSIONS FROM CONSUMER PRODUCTS" for the State of California.

Consumer Product Safety Act Certificaton.

This product was evaluated by Four Star Chemical and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location identified on the MSDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.